



KIEN2000B

8 Port Unmanaged
Industrial Ethernet Switch

UL, CE, FCC, RoHS,
Chinese State Grid
Certification

Physical Characteristics

Casing: Ribbed aluminum case (fanless)
Protection class: IP40
Installation: DIN-Rail or wall mounting
Dimensions(WxHxD): 55.4x139x119.5 mm (2.18x5.47x4.70 in.)
Weight: 0.6kg (1.323 pound)

Environmental Limits

Operating Temperature: -40 to 85°C (-40 to 185°F)
Storage Temperature: -40 to 85°C (-40 to 185°F)
Ambient Relative Humidity: 0 to 95% (non-condensing)

Approvals

IEC61000-4-2 (ESD): ±4KV contact discharge, ±8KV air discharge
IEC61000-4-3 (RS): 10V/M (80-1000MHz)
IEC61000-4-4 (EFT): power line ±2KV, data line ±1KV
IEC61000-4-5 (Surge): power line ±2KV CM/±1KV DM, data line ±1KV
IEC61000-4-6 (CS): 3V (10KHZ-150KHZ), 10V (150KHZ-80MHZ)
IEC61000-4-8 (Power frequency magnetic field): 100A/m cont. 1000A/m, 1s to 3s
IEC61000-4-12/18 (Damped oscillatory wave): 2.5KV CM, 1KV DM
IEC61000-4-10 (Damped oscillatory): 30A/m
IEC61000-4-16 (Common mode conduct): 30V cont. 300V, 1s
FCC CFR47 Part 15/EN55022: Class A&B
IEC61000-6-2 (Industrial Standards), EN50121-4 (Railway Applications)

UL, CE, FCC, RoHS, Chinese State Grid Certification

MTBF

35 years

Warranty

5 years

Overview

The KIEN2000B is an unmanaged industrial Ethernet switch. It offers 1 or 2 100Base-FX ports and 6 10/100Base-T(X) ports. With the plug-and-play feature, it is started up shortly, KIEN2000B offers dual redundant DC power inputs.

Features

1. Supports 1 or 2 100Base-FX port(s) and 6 10/100Base-T(X) RJ45 ports
2. Complies with EMC industrial level 4 regulated in IEC61850-3 standard
3. Ribbed aluminum case for heat dissipation (patent), fanless design
4. Operating Temperature: -40 to 85°C (-40 to 185°F)
5. DIN Rail or wall mounting
6. IP40 protection class

Technical Specifications

Standard

IEEE802.3
IEEE802.3u
IEEE802.3x
Store and forward switching mode

Network

Chain and star network topology

Interface

100M Fiber Ports: 1 or 2 x 100Base-FX port(s), SM/MM, FC/SC/ST
10/100M Copper Ports: 6 x 10/100Base-T(X) ports, RJ45
LED Indicators: RUN1, RUN2, PWR1, PWR2, LINK/ACT, 10M/100M


Cable

Twisted Pair: 0-100m (Standard CAT5, CAT5e network cable)
Multi Mode Fiber: 1310nm, 0-5km
Single Mode Fiber: 1310nm, 0-40km; 1550nm, 0-80km

Power Requirements

Power input: 12VDC/24VDC (9-36VDC), 48VDC (36-72VDC), 110VDC (70-140VDC), 220VDC (154-370VDC), dual redundant power inputs; 110VAC (85-165VAC), 220VAC (110-265VAC), single power input
Power terminal: 3-Pin 3.81mm-spacing plug-in terminal block
Power consumption: <6W

Mechanical Drawing



Ordering Information

Model	Description
KIEN2000B-S-6T	Unmanaged Ethernet switch with 1 100Base-FX ports, single mode, FC/SC/ST connector, 6 10/100Base-T(X) ports, RJ45 connector, DIN-Rail, 12VDC/24VDC (9-36VDC), 48VDC (36-72VDC), 110VDC (70-140VDC), 220VDC (154-370VDC), dual redundant power inputs; 110VAC (85-165VAC), 220VAC (110-265VAC), single power input, -40 to 85°C operating temperature, not supporting ring topology
KIEN2000B-M-6T	Unmanaged Ethernet switch with 1 100Base-FX ports, multi mode, FC/SC/ST connector, 6 10/100Base-T(X) ports, RJ45 connector, DIN-Rail, 12VDC/24VDC (9-36VDC), 48VDC (36-72VDC), 110VDC (70-140VDC), 220VDC (154-370VDC), dual redundant power inputs; 110VAC (85-165VAC), 220VAC (110-265VAC), single power input, -40 to 85°C operating temperature, not supporting ring topology
KIEN2000B-2S-6T	Unmanaged Ethernet switch with 2 100Base-FX ports, single mode, FC/SC/ST connector, 6 10/100Base-T(X) ports, RJ45 connector, DIN-Rail, 12VDC/24VDC (9-36VDC), 48VDC (36-72VDC), 110VDC (70-140VDC), 220VDC (154-370VDC), dual redundant power inputs; 110VAC (85-165VAC), 220VAC (110-265VAC), single power input, -40 to 85°C operating temperature, not supporting ring topology
KIEN2000B-2M-6T	Unmanaged Ethernet switch with 2 100Base-FX ports, multi mode, FC/SC/ST connector, 6 10/100Base-T(X) ports, RJ45 connector, DIN-Rail, 12VDC/24VDC (9-36VDC), 48VDC (36-72VDC), 110VDC (70-140VDC), 220VDC (154-370VDC), dual redundant power inputs; 110VAC (85-165VAC), 220VAC (110-265VAC), single power input, -40 to 85°C operating temperature, not supporting ring topology

Power supply: 12VDC/24VDC, 48VDC, 110VDC, 220VDC, dual redundant power inputs,
110VAC, 220VAC single power input

Power supply: 24VDC, 110VAC/220VAC, single power input

Please visit our website: www.kyland.cn for the latest updates.